

10,000 Super Pro Farm Rules 2026-2028

New rules in Red.

Temple Brizendine

Phone 804-443-1903

Email: temple.brizendine@yahoo.com

1. Diesel Tractors only.
2. No Billet Injection pumps. Maximum pump size is 3000 series 13 mm P Pump. It must have 2 springs on throttle linkage at pump in case cable breaks, it will pull it back to idle. A 14 mm A pump will still be allowed.
3. Tractor make of motor, chassis and transmission to match brand of tractor. OEM head, block, transmission and rear end or manufactures' replacement. Gear boxes will be allowed as long as they are inside the OEM housing
4. 540 cubic inch engine limit.
5. Intercoolers and water injection allowed.
6. Recast heads will be allowed with factory specs only.
7. All members may collect points.
8. **One (1) turbo charger with 3.2" inlet with all air entering in through the 3.2" inlet or a 3.2" restrictor which can be no more than 2" forward of the compressor wheel. Inlets will be checked with a 3.220 plug.**
9. Exhaust has to be at least 18" above the hood.
10. All vehicles running turbos must have exhaust bolts. In a cross pattern, 2-1/2" bolts or 4-3/8" Grade 8 bolts must be added as close to the exhaust housing as possible.
11. You must have side shields in order to pull.
12. Must have metal shield around turbo if running a fiberglass hood.
13. No factory steel fans. Must have electric or none.
14. Minimum drawbar length is 18" which is to be measured from center of rear axle. Maximum height is 20" and must be rigid in all directions.
15. All tractors will require Air shut off for sled to hook to and one for driver to pull, scatter blanket for clutch housing. Clutch must have all steel components, SFI approved.
16. Wheelie bars with minimum 5" square pads and 12" high bumper bars and maximum of 10" off ground and must extend out past the rear tires. They must support weight of tractor.
17. All Tractors must have a roll cage
18. Dead man's throttle required.
19. Front axle skid bars mandatory.
20. Maximum tire width is 24.5" and rim diameter is maximum 32". Puller 2000 and Old Style Firestone 10-ply Puller are allowed. No Mitas, Pro Pullers, Parkes Puller, nor Ag Tires are allowed.
21. All tractors must have working rear brakes.
22. All tractors must have fenders and hood.
23. The frame and weights must not extend any further than 13 feet from the center of rear axle excluding tow hook.
24. No Propane or Nitrous Oxide allowed
25. No advantages for 466 tractors. They must run same weight and turbo as rest of class.
26. All drivers must wear helmet, fire-approved suit, and SFI-certified neck collar.
27. Weighing in at 10,000 lbs maximum including ice.
28. Rules will be locked in for 3 years unless entire class sees something that needs to be addressed.